

Appendix 13

Specification of Seabirds Mitigation Measures in the WCPFC Convention Area

1. Tori lines (South of 30° South)

1a) For vessels ≥ 35 m total length

- i. Deploy at least 1 tori line. Where practical, vessels are encouraged to use a second tori line at times of high bird abundance or activity; both tori lines shall be deployed simultaneously, one on each side of the line being set. If two tori lines are used, baited hooks shall be deployed within the area bounded by the two tori lines.
- ii. A tori line using long and short streamers shall be used. Streamers shall be: brightly coloured, a mix of long and short streamers.
 - a. Long streamers shall be placed at intervals of no more than 5m, and long streamers must be attached to the line with swivels that prevent streamers from wrapping around the line. Long streamers of sufficient length to reach the sea surface in calm conditions must be used.
 - b. Short streamers (greater than 1m in length) shall be placed no more than 1m apart.
- iii. Vessels shall deploy the tori line to achieve a desired aerial extent greater than or equal to 100m. To achieve this aerial extent the tori line shall have a minimum length of 200m, and shall be attached to a tori pole >7 m above the sea surface located as close to the stern as practical.
- iv. If vessels use only one tori line, the tori line shall be deployed windward of sinking baits.

1b) For vessels <35 m total length

- i. A single tori line using either long and short streamers, or short streamers only shall be used.
- ii. Streamers shall be: brightly coloured long and/or short (but greater than 1m in length) streamers must be used and placed at intervals as follows:
 - a. Long streamers placed at intervals of no more than 5m for the first 75 m of tori line.
 - b. Short streamers placed at intervals of no more than 1m.
- iii. Long streamers should be attached to the line in a way that prevent streamers from wrapping around the line. All long streamers shall reach the sea-surface in calm conditions. Streamers may be modified over the first 15 m to avoid tangling.
- iv. Vessels shall deploy the tori line to achieve a minimum aerial extent of 75 m. To achieve this aerial extent the tori line shall be attached to a tori pole >6 m above the sea surface located as close to the stern as practical. Sufficient drag must be created to maximise aerial extent and maintain the line directly behind the vessel during crosswinds. To avoid tangling, this is best achieved using a long in-water section of rope or monofilament.

- v. If two tori lines are used, the two lines must be deployed on opposing sides of the main line.

2. Tori lines (North of 23° North)

2a) Long Streamer

- i. Minimum length: 100 m
- ii. Must be attached to the vessel such that it is suspended from a point a minimum of 5m above the water at the stern on the windward side of the point where the hookline enters the water.
- iii. Must be attached so that the aerial extent is maintained over the sinking baited hooks.
- iv. Streamers must be less than 5m apart, be using swivels and long enough so that they are as close to the water as possible.
- v. If two (i.e. paired) tori lines are used, the two lines must be deployed on opposing sides of the main line.

2b) Short Streamer

- i. Must be attached to the vessel such that it is suspended from a point a minimum of 5m above the water at the stern on the windward side of a point where the hookline enters the water.
- ii. Must be attached so that the aerial extent is maintained over the sinking baited hooks.
- iii. Streamers must be less than 1m apart and be 30 cm minimum length.
- iv. If two (i.e. paired) tori lines are used, the two lines must be deployed on opposing sides of the main line.

3. Side setting with bird curtain and weighted branch lines

- i. Mainline deployed from port or starboard side as far from stern as practicable (at least 1m), and if mainline shooter is used, must be mounted at least 1m forward of the stern.
- ii. When seabirds are present the gear must ensure mainline is deployed slack so that baited hooks remain submerged.
- iii. Bird curtain must be employed:
 - Pole aft of line shooter at least 3m long;
 - Minimum of 3 main streamers attached to upper 2m of pole;
 - Main streamer diameter minimum 20mm;
 - Branch streamers attached to end of each main streamer long enough to drag on water (no wind) – minimum diameter 10mm.

4. Night setting

- i. No setting between nautical dawn and before nautical dusk.
- ii. Nautical dusk and nautical dawn are defined as set out in the Nautical Almanac tables for relevant latitude, local time and date.

- iii. Deck lighting to be kept to a minimum. Minimum deck lighting should not breach minimum standards for safety and navigation.

5. Weighted branch lines

- i. Following minimum weight specifications are required:
 - one weight greater than or equal to 40g within 50cm of the hook; or
 - greater than or equal to a total of 45g attached to within 1 m of the hook; or
 - greater than or equal to a total of 60g attached to within 3.5 m of the hook; or
 - greater than or equal to a total of 98g weight attached to within 4 m of the hook.

6. Management of offal discharge

- i. Either no offal discharge during setting or hauling;
- ii. Or strategic offal discharge from the opposite side of the boat to setting/hauling to actively encourage birds away from baited hooks.

7. Blue-dyed bait

- i. If using blue-dyed bait it must be fully thawed when dyed.
- ii. The Commission Secretariat shall distribute a standardized colour placard.
- iii. All bait must be dyed to the shade shown in the placard.

8. Deep setting line shooter

Line shooters must be deployed in a manner such that the hooks are set substantially deeper than they would be lacking the use of the line shooter, and such that the majority of hooks reach depths of at least 100 m.