

## Annex: Management Methods for Storage, Clearance, and Disposal of Asbestos Tiles Waste from Building Demolition

1. "Asbestos Tiles" refers to the corrugated asbestos tiles, corrugated asbestos boards, and materials containing asbestos as listed in the "Report on Whether Demolished Objects Contain Asbestos" annexed to the "Demolition Directions for Buildings" of the Ministry of the Interior.
2. The asbestos tiles waste from building demolition shall comply with the relevant regulations of the Standards for the storage, clearance and disposal of hazardous industrial waste.
3. After the asbestos tiles waste from buildings is demolished, it shall be moistened first, and then packed in double layers of plastic bags with a thickness of not less than 60/10,000 centimeters for each layer. The openings shall be tightly tied, then the bag mouth shall be folded down and tied again before being placed in sturdy containers. Thus, it may be recognized as general industrial waste.
4. If the asbestos tiles waste from building demolition is recognized as general industrial waste, it shall comply with the following regulations:
  - I. Its storage shall comply with Articles 5, 6 and 10.
  - II. Its clearance shall comply with Articles 13 through 15.
  - III. Its intermediate treatment may adopt solidification, thermal treatment methods, or chemical treatment methods pursuant to Article 2, Paragraphs VI, VIII and X. However, the asbestos content after thermal treatment or chemical treatment shall be less than 1%.
  - IV. Its intermediate treatment facilities, industrial waste disposal organizations, or reuse organizations shall comply with Articles 23, and 26 through 29.
  - V. Its final disposal shall comply with Articles 34 through 37, and 41.